

TRACTOR ATTACHMENTS

| TRACTOR | 4025 2WD | 4025 4WD | 4525 2WD | 5525 2WD | 6525 2WD |
|---|---------------|---------------|---------------|----------|--------------|
| LOADER | ML333 | ML334 | ML333 | | ML253 |
| Maximum Lift Height | | 116.6" | | | 122" |
| Clearance with Attachment Dumped | | 90.6" | | | 98.5" |
| Reach at Maximum Height | | 21.3" | | | 28.5" |
| Maximum Dump Angle | | 34° | | | 39° |
| Attachment Rollback Angle | | 41° | | | 24° |
| Digging Depth Below Grade | | 3.8 | | | 6.5 |
| Lift Capacity to Full Height @ Pivot Pins | | 2866 | | | 3250 |
| Breakout Force @ Pivot Pins | | 4978 | | | 5300 |
| Rated Flow (Tractor System) | | 8.29 gpm | | | 10.5 gpm |
| Attachment Width | 60" | 72" | 60" | | 72" |
| Attachment Rated Capacity | 12.36 cu. ft. | 13.42 cu. ft. | 12.36 cu. ft. | | 16.3 cu. ft. |
| Cycle Times @ rpm | | 2500 | | | 2300 |
| Raise Boom (seconds) | | 6.2 | | | 7.0 |
| Lower Boom (seconds) | | 4 | | | 5.5 |
| Dump Attachment (seconds) | | 2.7 | | | 4.0 |
| Retract Attachment (seconds) | | 2.7 | | | 3.0 |
| BACKHOE MODEL | ANBH86 | | | | N/A |
| TRANSPORT | | | | | |
| Transport Height | 90" | | | | N/A |
| Transport Overhang | 58" | | | | N/A |
| OPERATIONAL | | | | | |
| Maximum Digging Depth | 105" | | | | N/A |
| Digging Depth (2 Ft.) Flat Bottom | 100.6" | | | | N/A |
| Overall Operating Height - Fully Raised | 120.8" | | | | N/A |
| Loading Height (bucket @ 60°) | 98" | | | | N/A |
| Loading Reach (bucket @ 60°) | 62.9 | | | | N/A |
| Reach From Swing Post | 135" | | | | N/A |
| Bucket Rotation | 108° | | | | N/A |
| Swing Arc | 108° | | | | N/A |
| Stabilizer Spread Operating Position | 86" | | | | N/A |
| Stabilizer Down Below Grade | 3.6" | | | | N/A |
| System Relief Valve Setting (psi) | 2350 | | | | N/A |
| Digging Force - Bucket (lbs.) | 3670 | | | | N/A |
| Digging Force - Dipper (lbs.) | 2310 | | | | N/A |

Optional Attachments
including, but not limited to -

- Bucket
- Bale spear
- Pallet fork

TRACTOR SPECIFICATIONS



| TRACTOR | 4025 2WD | 4025 4WD | 4525 2WD | 5525 2WD | 6525 2WD |
|---|---|--------------------------|--------------------------|--|---------------------------|
| ENGINE | | | | | |
| Type | Four stroke, direct injection water-cooled, diesel | | | Four stroke, direct injection, turbo-charged and intercooled, diesel | |
| Cylinders | 4 | | | 3 | |
| Engine HP (kW) @ rpm | 41 (30.5) @ 2300 | | 46 (34.3) @ 2300 | 55 (40.3) @ 2100 | 62 (46.2) @ 2100 |
| Compression Ratio | 19.5:1 | | | 17.2:1 | |
| Displacement cubic inch ³ (cc) | 167 (2732) | | | 152.4 (2497) | |
| Fuel Tank Capacity | 14.55 gallons | | | 14.8 gallons | |
| ELECTRICAL | | | | | |
| Battery Capacity | 12 volt, 96 amp hours | | | | |
| Alternator | 12 volt, 36 amps | | | | |
| CLUTCH | | | | | |
| Type | Dual | | | Dual dry with ceremetallic lining | |
| TRANSMISSION | | | | | |
| Type | Sliding mesh | | | Partial constant mesh | Full constant mesh |
| Number of Gears / Speeds | 8F / 2R | | | | |
| Max Speed Forward / Reverse mph (kmph) | 14.3 (23.1) / 6.0 (9.6) | 17.6 (28.3) / 7.5 (12.1) | 15.2 (24.4) / 6.3 (10.2) | 18.3 (29.3) / 7.7 (12.3) | 19.8 (31.8) / 10.6 (17.1) |
| STEERING | | | | | |
| Type | Hydrostatic Power | | | | |
| Pump Output (gallons per minute) | 5 | | | 4.8 | |
| BRAKES | | | | | |
| Type | Fully enclosed dry disc | | | | |
| HYDRAULIC SYSTEM | | | | | |
| Type | Open center, full-live hydraulic with position and draft controls | | | | |
| Pump Output (gallons per minute) | 8.29 | | | 10.5 | |
| 3-Point Linkage | Category 1 and 2 adjustable, with telescopic stabilizers | | | | |
| Lift Capacity (lbs.) | 3527 | 3525 | | 3527 | |
| Rear Auxiliary Remote Valves | 1 spool optional | | | 1 or 2 spool optional | |
| PTO | | | | | |
| Type | Live | | | | |
| PTO RPM (engine rpm) | 540 @ 2058 | | | 540 @ 2059 | |
| PTO HP (kW) | 31 (23.1) | | 36 (26.9) | 45 (33.6) | 52 (38.8) |
| OPERATING WEIGHT | | | | | |
| Total (lbs.) | 4389 | 4950 | 4425 | 4836 | 4928 |
| DIMENSIONS with Ag Tires | | | | | |
| Overall Length Inches (mm) | 115.3 (2928) | 129 (3276) | 116.3 (2954) | 119.0 (3022) | |
| Overall Width Inches (mm) | 69.4 (1762) | 82 (2082) | 70 (1778) | 78.0 (1981) | 78.0 (1981) |
| Overall Height Inches (mm) | 88.0 (2235) | 93.7 (2380) | 89.0 (2261) | 94.0 (2388) | 95.0 (2413) |
| Turning Radius Minimum Feet (meters) | 9.6 (2.9) | 10.5 (3.2) | | 9.6 (2.9) | |
| TIRES Sizes and Options | | | | | |
| Ag (Front / Rear) | 6x16 / 12.4x28 | 9.5x16 / 12.4x28 | 6x16 / 13.6x28 | 7.5x16 / 13.6x28 | 7.5x16 / 14.9x28 |
| Industrial (Front / Rear) | N/A | 12x16.5 / 16.9x24 | N/A | N/A | N/A |

25 Series



**SUPERIOR
PERFORMANCE
DAY IN AND
DAY OUT**



5525 2WD



6525 2WD

9020 JACKRABBIT RD., Suite 600 • Houston, Texas 77095 • 877-449-7771

MahindraUSA.com • MahindraCanada.ca
© 2013 Mahindra USA MAH-0413 MAH51XXXX



#1 Selling Tractor in the World

Mahindra
Rise.

AVAILABLE IMPLEMENTS

Mahindra offers a huge selection of implements to help you accomplish whatever task you wish to tackle and provide a complete Mahindra experience.

- Wide array of implements (186 variations)
- Competitive financing terms
- Standard-, Medium-, and Heavy-Duty implements to meet your needs
- Implements feature rugged construction with heavy-duty components
- 5 year gearbox limited warranty
- SNOW BLOWERS and SNOW REMOVAL equipment to meet cold-weather needs
- BEST VALUE in the market today



ECONOMY - 25 Series

The Mahindra 25 series tractors are rugged and hard-working 2WD and 4WD (4025 only) utility tractors designed for light- to medium-duty applications. These practical, no-nonsense models are available from 40 to 65 HP and with a wide range of available implements that provides you with everything you need to get your work done.

Key Features:

- Fuel efficient, low RPM 3 & 4 cylinder engines
- Larger tires for better traction and stability
- Heavy operating weight for built in safety
- Best-in-class loader and 3-point lift capacities
- Heavy-gauge steel fenders and hood
- Hydrostatic power steering
- Live 540 rpm PTO
- STANDARD rear work light
- STANDARD rubber floor mat
- STANDARD 5-year limited warranty - Industry's Best

Ideal For:

- Speciality / Hobby Farming
- Material Handling
- Grounds Maintenance / Municipal
- Rural Lifestyle



Engine - left side view

- Tackle the toughest jobs with the 25 Series rugged diesel engine
- One piece hood - easy access for maintenance



Rugged design

- All metal hood and fenders
- Protects from brush and obstacles
- Heavy-duty styling



Platform

- Conveniently placed controls
- Thick rubber floor mat provides ergonomic working area
- Easy access platform - even with loader



Dash panel

- Dependable 2 stage clutch
- Easy to read gauges provide all the info you need at a glance
- Easy to grip, comfortable levers and handles

SUPERIOR PERFORMANCE. GREATER VALUE.

- Superior lift capacity = Lift heavier loads
- 5 year warranty = Peace of mind
- Professional grade construction = Bigger, thicker, more solid components
- Heavier, sturdier chassis = Greater traction, stability & safety

