

MAHINDRA 7060 4WD

PERFORMANCE & POWER

67 ENGINE HP • 57 PTO HP

FULL-SIZE UTILITY TRACTOR

Modern-looking workhorse for all-purpose farming and ag, grounds maintenance and organic and specialty farming.

- #1 selling tractor in the world
- 5-year powertrain warranty
- Attractive Financing Options
- Heavy-duty cast-iron chassis

- Professional grade components
- Japan Quality Medal Winner
- Deming Award Winner
- Industry-leading parts support



Mahindra

TRACTOR 7060 4WD

ENGINE	
Type	Turbocharged, four stroke, inter-cooled, direct injection, diesel
Cylinders	3
Cylinder Sleeve	Wet replaceable
Engine HP (kW) @ rpm	67 (49.98) @ 2200 rpm
Compression Ratio	17.2:1
Displacement cubic inch (cc)	152.4 (2497)
Fuel Tank Capacity	19.3 gallons
ELECTRICAL	
Battery Capacity	12 volt, 96 amps
Alternator	12 volt, 55 amps
CLUTCH	
Type	Dual dry with ceremetallic lining
TRANSMISSION	
Type	Forward-Reverse synchro shuttle with full synchromesh
Number of Gears / Speeds	12F / 12R
STEERING	
Type	Hydrostatic power with tiltable column
Pump Output (gallons per minute)	5.1
BRAKES	
Type	Wet disc
HYDRAULIC SYSTEM	
Type	Open-center, full-live hydraulic with position and draft controls
Pump Output (gallons per minute)	11
3-Point Linkage	Category 2 ball joints with telescopic lower links and stabilizers
Lift Capacity (lbs.)	5100
Rear Auxiliary Remote Valves	Standard 2 spool with detent in raise, lower and float position. Kickback in raise and lower.
PTO	
Type	Independent
PTO RPM (engine rpm)	540 @ 2186
PTO HP (kW)	57 (41.9) max
OPERATING WEIGHT	
Total (lbs.)	6727
DIMENSIONS With Industrial Tires	
Overall Length Inches (mm)	157.63 (4004)
Overall Width Inches (mm)	77.3 (1963.5)
Turning Radius Minimum feet (meters)	13 (3.96)
TIRES Sizes & Options	
Ag (Front / Rear)	9.5x24 / 16.9x28
Industrial (Front / Rear)	12.5/80x18 / 19.5Lx24



LOADER ML272

WITH TRACTOR MODEL 7060 4WD	
Maximum Lift Height	132"
Clearance with Attachment Dumped	106"
Reach at Maximum Height	26"
Maximum Dump Angle	39°
Attachment Rollback Angle	20°
Digging Depth Below Grade	5"
Lift Capacity to Full Height @ Pivot Pins (lbs.)	3460
Breakout Force @ Pivot Pins (lbs.)	5640
Rated Flow (Tractor System)	11 gpm
Attachment Width used for specification	78"
Attachment rated capacity used for specification	19 cu. ft.
Cycle Times @ rpm	2200 rpm
Raise Boom (seconds)	6.1
Lower Boom (seconds)	4.5
Dump Attachment (seconds)	5
Retract Attachment (seconds)	3.7
Loader Shipping Weight (lbs.)	1900
OPTIONAL / SKID STEER ATTACHMENTS	
Grille Guard (with or without loader)	✓
Bucket	✓
Bale Spear	✓
Pallet Fork	✓

BACKHOES

WITH TRACTOR MODEL 7060 4WD	
Backhoe Models	509 / 511
TRANSPORT	
Shipping Weight with 12" bucket (lbs.)	1425 / 1594
Transport Height (boom fully retracted)	93" / 106"
Transport Width (stabilizers up)	60"
Boom Pivot Height	16"
Overall Length	91" / 93"
OPERATIONAL	
Maximum Digging Depth	116" / 133"
Digging Depth (2 Ft.) Flat Bottom	115" / 132'
Digging Depth (8 Ft.) Flat Bottom	99" / 119"
Overall Operating Height - Fully Raised	154" / 173"
Loading Height	82" / 96"
Loading Reach	50" / 60"
Reach From Swing Post	153" / 173"
Bucket Rotation	180°
Swing Arc	180°
Stabilizer Spread Operating Position	95"
Stabilizer Down Below Grade	16"
System Relief Valve Setting (PSI)	2500
Digging Force - Bucket (lbs.)	5676
Digging Force - Dipper (lbs.)	2754 / 3056