

# ▶ Sprayers

RedMax offers premium commercial-duty sprayers that can handle the most demanding conditions. The patented design also reduces maintenance and removes all possibility of leaks. All RedMax sprayers utilize high-pressure piston pumps. Diaphragm pumps utilized by the competition cannot provide high-pressure capability. By comparison, RedMax sprayers will spray up to 25 feet. All units include premium spray pistols with brass shut-off valves and the highest grade double Nytrol O-rings. All models feature ergonomically-designed canister handles and brass spraying wands to enhance user comfort over extended periods of time. As an added convenience, the overall design makes for easy assembly or disassembly in the field. All models feature thick-walled, heavy-duty polyethylene tanks that are UV-stabilized with UV inhibitors for years of service in sunlight.



Sprayer Usage Guide			
Model Name	HM20	BM40S	BM46I
Herbicide	●	●	●
Insecticides	●	●	●
Fertilizers	●	●	●
Chlorine (5%)	●	▲	●
Diesel	●	●	●
Wettable Powder	n/a	n/a	●
Stains & Sealers	●	●	●
Oil Based	●	●	●
Solvent Based	●	●	●

● = Acceptable ▲ = Acceptable If cleaned

**WARNING!**  
RedMax Sprayers are NOT DESIGNED to be used with caustic materials including stripping compounds, acids or any solution that may be FLAMMABLE or generate its own HEAT.

## ▼ HM20



- 2.0 gallon working capacity with 4.5" opening
- 42 PSI (high-pressure capability)
- Industrial 47" hose with 20" brass wand
- Strainer-installed wand
- Solid-steel pump rod
- No tools required for disassembly
- VITON™ seal and Nytrol O-rings allows use of harsh chemicals
- Chlorine use available with proper cleaning
- Thick-walled, UV-protected tank

## ▼ BM40S



- 4.0 gallon working capacity with 6" opening
- 150 PSI (high-pressure w/safety check valve)
- Ergonomic and foldable handle can be set for right- or left-hand use
- Strainer-installed wand
- High-pressure, leak-proof sealed and maintainable piston pump
- Wide 1.5" strap w/ pad for increased comfort
- Lid includes carting handle and wand clip
- VITON seal and Nytrol O-rings for long, leak-proof life
- Chlorine use available with proper cleaning

## ▼ BM46i



- 4.6 gallon working capacity with 6" opening
- 168 PSI (high-pressure internal pump eliminates external leaks)
- 20" brass wand with brass adjustable nozzle
- Lid includes carting handle and wand clip
- Ergonomic, steel-tube handle
- Includes built-in paddle agitation for wettable powders
- VITON seal and Nytrol O-rings
- Chlorine use available with proper cleaning
- No tools required for disassembly

### Sprayer Accessories

<p><b>Adjustable Brass Nozzle with Holder</b> (PN 574 15 28-01)</p>	<p><b>Z-Nozzle Brass Boom</b> (PN 574 15 72-01)</p>	<p><b>Lager Spray Shield</b> (PN 574 15 70-01)</p>	<p><b>Telescoping Wand (23" - 37")</b> (PN 574 15 57-01)</p>	<p><b>Brass Extension Wand</b> (66" - PN 574 15 43-01) (26" - PN 574 15 48-01)</p>
<p><b>Universal Gun Brass Wand w/ Adjustable Nozzle</b> (PN 574 15 51-01)</p>	<p><b>Adjustable Plastic Nozzle</b> (PN 574 15 56-01)</p>	<p><b>Small Spray Shield</b> (PN 574 15 71-01)</p>	<p><b>Plastic Spray Tip Set</b> (PN 574 15 39-01)</p>	<p><b>NEW Padded Shoulder Strap for BM46i</b> (PN 574 16 24-01 = one strap)</p>

Model	Part Number	Tank Capacity	Max Pressure	Dry Weight	Warranty	
(50 States)		(Gal.)	(Psi)	(Lbs)	(Cons.)	(Com.)
HM20	574 14 31-01	2.0	42	8.2	2 Yrs.	1 Yr.
BM40S	574 11 40-01	4.0	150	13	2 Yrs.	1 Yr.
BM46I	574 11 41-01	4.6	168	15	2 Yrs.	1 Yr.