



## Trimmer Line

The heavy-duty round nylon line is designed for commercial use and made of specially formulated and custom-blended co-polymers. The high-tensile strength of our unique round lines makes them last up to 30% longer when compared to standard round lines. Our patented Cable Twist™ trimmer line provides less air resistance reducing drag and allowing the engine to reach top RPM more quickly. This increases operator comfort and reduces fuel consumption.



PT104 Plus with Cable Twist™ shown above

Part Number By Diameter					
Type	Size	0.080	0.095	0.105	0.130
Round	1 Lb. Donut	574 14 59-01	574 14 60-01	574 14 61-01	574 14 62-01
Round	3 Lb. Spool	574 14 63-01	574 14 64-01	574 14 65-01	574 14 66-01
Round	5 Lb. Spool	574 14 67-01	574 14 68-01	574 14 70-01	574 14 71-01
Cable Twist™	0.8 Lb. Donut	574 13 11-01	574 13 12-01	574 13 13-01	574 13 14-01
Cable Twist™	2.4 Lb. Spool	574 13 17-01	574 13 18-01	574 13 19-01	574 13 20-01
Cable Twist™	4 Lb. Spool	574 13 21-01	574 13 22-01	574 13 24-01	574 13 25-01

## Cutting Heads



Model	MT104R 4" Tap & Go	MT104 4" Tap & Go	PT104 4" Tap & Go	PT104 Plus 4" Tap & Go	MSL100 4" Tap & Go	PT100 6" Tap & Go	PFL100 5" Fix Line	UBT100 3" Tap & Go	UBT200 4" Tap & Go
Part Number	537 33 83-07	537 33 83-06	521 47 21-02	970 37 09-01	574 14 35-01	970 36 87-01	970 36 89-01	574 16 51-01	574 16 57-01



BT280	●	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
BC280	n/a	●	◆	◆	◆	n/a	◆	◆	◆
TR2350S	n/a	◆	◆	●	◆	n/a	◆	◆	◆
BCZ2460S/TS	n/a	◆	◆	●	◆	n/a	◆	◆	◆
BCZ2450T	n/a	n/a	◆	n/a	●	n/a	◆	n/a	n/a
BCZ2650S/2660TS	n/a	◆	◆	●	◆	n/a	◆	◆	◆
BCZ2650T	n/a	n/a	◆	n/a	●	n/a	◆	n/a	n/a
BCZ3050S	n/a	◆	◆	●	◆	n/a	◆	◆	◆
BCZ3060TS	n/a	◆	◆	●	◆	n/a	◆	◆	◆
BCZ3050SW	n/a	◆	◆	●	◆	n/a	◆	◆	◆
BC4401DW	n/a	◆	◆	◆	◆	●	◆	◆	◆
BC-EX2	n/a	◆	◆	●	◆	n/a	◆	◆	◆

● = Standard    ◆ = Optional    n/a = Non Applicable

# ▶ Protective Gear & Oil

RedMax protective gear provides superior comfort and performance in the field. MaxLife Engine Oil is specifically designed for high-RPM, lean-burning, air-cooled 2-stroke engines. Our synthetic blend oil formulation is considered a top performer amongst outdoor power equipment professionals.

## ▼ Safety Gear



Includes high-quality earmuffs with a noise reduction rating of 22dB(A), an optional mesh visor attachment and a safety helmet with both the earmuffs and mesh visor attached.

*(Helmet System: Part Number 574 14 48-01)*

*(Visor: Part Number 574 14 43-01)*

*(Headset: Part Number 574 14 44-01)*

## ▼ Safety Glasses



Meets all applicable ANSI Z87.1-2003 performance and safety standards. All lenses filter out 99.9% of all harmful UV radiation. Available in gray or mirror lens.

*(Gray: Part Number 574 15 80-01)*

*(Mirror: Part Number 574 15 81-01)*

## ▼ Baseball Cap



Our black, low profile cap features an attractive design, quality construction and adjustable Velcro band.

*(Part Number 574 10 57-01)*

## ▼ MaxLife Engine Oil

MaxLife Engine Oil contains special additives to reduce piston, ring groove, and crankcase deposits. It also reduces the fuel oxidation that causes varnish, gum and stale fuel. Even exhaust port and spark arrestor screen blocking is minimized. As a result, engines run cooler, cleaner and with greater efficiency. This oil has a very low ash content, which reduces engine deposits and exhaust port plugging. It also contains fuel stabilizers that double fuel life.

MaxLife engine oil is available in seven sizes: 2.6 ounces, 5.2 ounces, 6.4 ounces, 13 ounces, 1 gallon, 5 gallon pail and 55 gallon drum. RedMax bar and chain oils are also available in quart and gallon sizes that are specially formulated with dispersers and tacifiers to maximize lubricity and reduce heat buildup from chain friction. Specially formulated for high-RPM Pro Series chain saws, they reduce the high-speed throw-off of oil and extend the bar and chain life.



001USZ001

FD

RedMax JASO-M345FD  
Certification/Registration Number

\*MaxLife engine oil is fully compatible with EPA and C.A.R.B. requirements and exceeds the highest ISO-LEGD and JASO M345/FD 2-stroke oil requirements. It is certified by and registered with JASO for use in ALL air-cooled, 2-stroke, outdoor power equipment engines.